Charger battery E2



Quick charger for 2,4V - 28,8V or rather 7,2V - 18,0V Ni-Cd/ Ni-MH/ Li-Ion Battery packs. Microprocessor-controlled charging, charging times 30-150 min. depending on the battery's capacity (1,5Ah - 7,5Ah).

Technical Data

Dimensions L1810 / L2410:	**152 x 86 x 76 mm**
Dimensions L1830 / L2430:	**150 x 85 x 75 mm**
Shutdown criteria:	**- U, Temperaturabschaltung**
Battery capacity:	**1,5Ah (2 Zellen) bis 7,5Ah (21 Zellen)**
Battery system:	**Ni-Cd/ Ni-MH/ Li-ION**
Output voltage L1810 / L1830:	**7,2V - 18,0V**
Output voltage L2410 / L2430:	**2,4V - 28,8V**
Operating temperature:	**+5°C - 40°C**
Input voltage EU Version:	**220-240V / 50Hz-60Hz**
Input voltage US Version:	**110-120V / 50Hz-60Hz**
Energy absorption:	**Standby < 1W, max. 70W**
Float charge:	**30 mA**
Charge current:	**max. 3,0 A**
Charge time:	**max. 150 min bei 7,5 Ah**
Storage temperature:	**-20°C - 60°C**
Weight:	**max. 0,5 kg**
Protection class:	**II**