

<b>LUKAS</b>	<b>eDRAULIC Cutter</b>				<b>EN</b>
	<b>S 799 e<sup>3</sup> 93-20-43</b>				
	Technical Data				
<i>Non-metric dimensions are for reference only.</i>					
<b>Nomenclature</b>		<b>Value</b>	<b>Unit</b>	<b>Remark</b>	
<b>Dimensions</b>	L x W x H	930 x 265 x 253 36.6 x 10.4 x 9.96	mm in.	closed; w/o battery	
<b>Cutting performance</b>		Ø45 Ø1.77	mm in.		
<b>Opening width at tips</b>		204 8.03	mm in.	at tips	
<b>Ambient temperature</b>		-20 ... +55 -4 ... +131	°C °F		
<b>Weight</b>		24,9 54.9	kg lbs.	incl. hydraulic fluid, w/o battery <i>incl. hydraulic fluid, w/o battery</i>	
<b>Weight battery 9 Ah</b>		1,6 3.6	kg lbs.		
<b>Weight battery 5 Ah</b>		1,2 2.7	kg lbs.		
<b>Protection class DIN EN 60529:2014-09</b>		IP 58		Up to 60 minutes and a depth of up to 3 meters	
<b>Opening / closing time</b>	>	2	s	w/o load	
<b>Noise pressure level</b>	idle mode max. load	69 74	dB(A) dB(A)		
<b>Rechargeable battery 1 / 2</b>		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory	
<b>Current consumption</b>		7,3 40	A A	idle mode max. load	
<b>EN 13204 Cutting performance</b>		1K-2K-3K-4K-5K			
<b>Operating pressure</b>		70 10,000	MPa psi		
<b>Note:</b>					
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.					
<b>LUKAS Hydraulik GmbH</b>	Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394				

Änderungen vorbehalten / Subject to revision